



2950 Mechanic Street, Lake City, PA 16423-2095

Phone: 814/774-2631 Or 800/840-9906

Order Fax: 814/774-3482 Corporate Fax: 814/774-0778 E-mail: info@vanairsystems.com

www.vanairsystems.com

U.S. Department of Labor Occupational Safety and Health Administration (non-mandatory form)

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

Date Prepared: January 1, 2009

Material Safety Data Sheet

Section 1 – Chemical Product Information

Product: Activated Alumina (1/8", 1/4", 3/16", 1/2" and Granular)

Part No.: 33-0237, 33-0238, 33-0240, 33-0241, 33-0266, 33-0267, 33-0268, 33-0281,

33-0320, 33-0321, 33-0367, 33-0370, 33-0371, 33-0372, 33-0373 & 33-268



Section 2 – Ingredients/Identity Information

Components			Other Limits		
(Specific Chemical Identity/Common Name(s))		OSHA PEL	ACGIH TLV	Recommended	% Optional
TWA in mg/m ³ unless indic	ated for alumina dust	: 15,5 (respirable)	10 (total)		
	<u>% Typical</u>				
$Al_2O_3 X H_2O$	90.0 - 97.0	CAS #1333-84-2			
*Na₂O	0.3 - 0.6				
*SiO ₂	0.01 - 0.2				
*Fe ₂ O ₃	0.03 - 0.1	*Expressed as oxide equivalent.			
Loss on ignition (water)	4.0 - 7.0	NOTE: Silicon exists within molecular structures only and does not exist as silicon dioxide			

Section 3 – Physical Chemical Characteristics

Boiling Point: Undetermined. Density: $38 - 52 \#/Ft^3$ Vapor Pressure (mm Hg): Not applicable. Freezing-Melting Point: 3,700 °F (2038 °C) Vapor Density (Air=1): N/A

Solubility in Water: Insoluble.
Evaporation Rate (Butyl Acetate=1): Not applicable.

Solubility in Acids and Alkalis: Soluble in concentrated acids and alkalis; pH: ~10 (20% slurry solution)

Appearance and Odor: Off-White pellets. Odorless.

Section 4 – Fire and Explosion Hazard Information

Flammable Properties

Flash Point: Not applicable. Method Used: Not applicable.

Flammability Limits

LEL: Not applicable. UEL: Not applicable.

Fire Fighting Instructions: NIOSH approved, positive pressure, self-contained breathing

apparatus and full protective clothing when appropriate.

Extinguishing Media: Use extinguishing agent applicable to surrounding fire.

Unusual Fire and Explosion Hazards: Not an explosion hazard. Not combustible.

Van Air Systems

Activated Alumina Material Safety Data Sheet Date Prepared: January 1, 2009

Page 2 of 2

Section 5 – Reactivity Information

Stability (Conditions to avoid): Stable. No decomposition if stored and applied as directed.

Incompatibility (Materials to avoid): Heating occurs when water is added.

Hazardous decomposition/byproducts: No dangerous decomposition products known.

Hazardous Polymerization: Will not occur.

Section 6 - Health Hazard Information

Potential Health Effects: Inhalation, skin and eye contact. Can cause mild irritation.

Health Hazards (acute and chronic): Alumina is a low health risk by inhalation and should be treated as a

nuisance dust as specified by ACGIH. TLV is 10 mg/m³.

Carcinogenicity: No. NTP: No. IARC Monographs: No. OSHA Regulated: No.

Emergency and First Aid Procedures

Eyes: Flush with water for at least 15 minutes. Skin: Wash with soap and warm water.

Inhalation: Remove to fresh air.

IF IRRITATION PERSISTS SEEK MEDICAL ATTENTION

Section 7 – Precautions for Safe Handling and Use

Small/Large Spills: Clean up using dry procedures; avoid dusting.

Waste Disposal Method: Collect in containers, bags or covered dumpster boxes. If reuse or

recycling is not possible, material may be disposed of at an industrial landfill. Not a RCRA Hazardous Waste. - Not federally regulated.

Handling & Storage: Avoid eye and skin contact. Do not inhale dust. Keep material dry.

Other precautions: Ensure good ventilation/exhaust, prevent formation of dust.

Section 8 – Control Measures

Respiratory Protection (specific type): NIOSH-approved dust respirators.

Ventilation: Use adequate ventilation.

Local, Mechanical, Special & Other Exhaust – Not applicable.

Protective Gloves: Wear gloves to avoid direct skin contact.

Eye Protection: Safety glasses.

Other Protective Clothing & Equipment: Use safety equipment when required. Work/Hygienic Practices: Wash thoroughly after handling.

Section 9 – Regulatory Information/References

All components of this product are listed on the TSCA Inventory (USA), WHMIS Domestic Substance List (Canada) and the EINECS Inventory (EC Market). For inventory reporting purposes, CAS# 1344-28-1 was assigned for aluminum hydroxide and activated alumina products. This material fits the EPA Hazard Category definition of Immediate (Acute) Health Hazard under SARA Sections 311, 312. For purposes of SARA III reporting, this substance contains no ingredients listed on the Extremely Hazardous, CERCLA, or Section 313 lists.

Not regulated by USA D.O.T. or Canadian TDG Hazard Class and PIN.

References – American Industrial Hygiene Association (AIHA) Hygienic Guide Series (revised June 1978); U.S. Dept of Health and Human Services; NIOSH; Registry of Toxic Effects of Chemical Substances, 1985-86 Edition; Sax, N. Irving: Dangerous Properties of Industrial Materials, Van Nostrand Reinhold Co. Inc., 1984. American Conference of Governmental Industrial Hygienists, Inc. (ACGIH), Documentation of the Threshold Limit Values & Biological Exposure Indices, Sixth Edition, 1992.